

GENSET RANGE AND SPECIFICATIONS

GENSET MODEL	ENGINE TYPE	PRIME RATING		ENGINE DATA						OPEN TYPE					SILENT TYPE				
				No. Of cyl.	Bore X Stoke (mm)	Piston Displ. (Ltr)	Fuel Consumption (L/H)		Oil Cap. (Ltr)	Approximate Dimension			Approx. Weight (kg)	Fuel Tank Cap. (Ltr)	Approximate Dimension			Approx. Weight (kg)	Fuel Tank Cap. (Ltr)
							75% Load	100% Load		L (mm)	W (mm)	H (mm)			L (mm)	W (mm)	H (mm)		
ED 85 V	TD 520 GE	85	68	4	108.0 x 130.0	4.760	13.60	18.11	13.0	2100	900	1900	1225	140	2750	1100	1300	1721	100
ED 100 V	TAD 531 GE	100	80	4	108.0 x 130.0	4.760	15.45	20.80	13.0	2250	900	1900	1282	140	2750	1100	1300	1768	120
ED 130 V	TAD 532 GE	130	104	4	108.0 x 130.0	4.760	20.48	27.82	13.0	2300	950	2100	1432	140	3200	1250	1550	2219	250
ED 150 V	TAD 731 GE	150	120	6	108.0 x 130.0	7.150	24.19	32.25	20.0	2750	950	2100	1678	200	3600	1350	1800	2672	250
ED 180 V	TAD 732 GE	180	144	6	108.0 x 130.0	7.150	28.76	38.34	34.0	2800	1000	2100	1865	200	3600	1350	1800	2774	250
ED 200 V	TAD 733 GE	200	160	6	108.0 x 130.0	7.150	32.10	43.20	34.0	2800	1000	2100	1940	200	3750	1400	1900	2738	300
ED 250 V	TAD 734 GE	250	200	6	108.0 x 130.0	7.150	38.29	48.00	29.0	3100	1100	2300	2204	400	4000	1500	2100	3136	400
ED 325 V	TAD 941 GE	325	260	6	120.0 x 138.0	9.360	48.75	65.65	33.0	3200	1200	2300	2764	400	4500	1500	2100	3787	450
ED 350 V	TAD 1342 GE	350	280	6	131.0 x 158.0	12.780	47.40	62.55	36.0	3200	1200	2300	3005	400	4500	1700	2100	4143	450
ED 375 V	TAD 1343 GE	375	300	6	131.0 x 158.0	12.780	50.79	67.37	36.0	3600	1200	2550	3214	400	4500	1700	2100	4284	500
ED 400 V	TAD 1344 GE	400	320	6	131.0 x 158.0	12.780	55.30	72.61	36.0	3600	1200	2550	3217	400	4500	1700	2100	4290	500
ED 500 V	TAD 1641 GE	500	400	6	144.0 x 165.0	16.120	73.50	99.50	48.0	3500	1250	2550	3730	400	5000	1800	2100	4937	600
ED 570 V	TAD 1642 GE	570	456	6	144.0 x 165.0	16.120	84.20	115.00	48.0	3500	1250	2550	3878	400	5000	1800	2100	5122	600
ED 630 V	TWD 1643GE	630	504	6	144.0 x 165.0	16.120	92.61	125.37	48.0	3600	1400	2550	4263	400	5000	1800	2100	5482	600

Note :

ALL DIMENSIONS LISTED ARE INCLUSIVE OF MUFFLER
AC GENERATORS, ALTERNATOR STAMFORD, BRUSHLESS GENERATORS, INSULATION CLASS H WITH AVR,
VOLTAGE 220/380 VOLT, 3 PHASE, 0.8PF, 50HZ, 1500RPM

Specification Subject To Change Without Notice

EKA DHARMA PT. EKA DHARMA JAYA SAKTI
Subsidiary of INDOMOBIL Group

Head Office

Kanto A. 18 Mega Glodok Kemayoran,
Jl. Angkasa Kav - B6 Kota Baru,
Bandar Kemayoran - Jakarta
Telp. +62 21 29371389
Fax. +62 2129371390

www.ekadharma.co.id

Regional Service Center

Jl. Jend. Sudirman No. 22 RT. 25 Kel. Damai
Bahagia, Balikpapan - Kalimantan Timur
Telp. +62 542 765555
Fax. +62 542 766441/765032/761605
email : bpp-gen@ekadharma.co.id /
volvopenta-gen@ekadharma.co.id

